



TH132 Series

This ultra-compact thermostat provides precise control of the ambient temperature



 [Print this page](#)

MODEL & RATINGS

TH132-A-230 3450 W @ 230 V 15 A resistive 50 Hz 4 wires / SPST

SPECIFICATIONS

TEMPERATURE CONTROL

Microprocessor-optimized PIA
Heating cycles: 15 minutes
Accuracy: $\pm 0.5^{\circ}\text{C}$ / 0.9°F

PROGRAMMING

7-day, 4 time periods/day, 2 temp. settings
Early Start function
24-hour clock / $^{\circ}\text{C}$ or $^{\circ}\text{F}$

DIMENSIONS (H•W•D)

82 x 78 x 25 mm / 3.2 x 3.1 x 1 inches

FEATURES

Compact design - one of the smallest, most attractive thermostats on the market

On-screen heating power indicator gives at-a-glance verification of power being used

Temporary bypass enables temperature override without changing programming

Large, easy-to-read LCD features intuitive programming icons


Battery-free backup means no re-programming your schedule after power outage

ACCESSORIES

Aube AC130-01 European floor sensor

INSTRUCTION MANUAL

 [TH132-A-F-AF-230.pdf](#) (format PDF)

 To view a PDF, you must have Acrobat Reader.
Click on the icon to download it for free.

WARRANTY

